

HOTSPOTTER

This all purpose propane flame tool operates off of the pressure of a standard propane tank—no regulator required. Appropriate for a wide variety of all-season maintenance/repair applications at commercial offices, factories, institutions, warehouses, parks, residential properties, farms and parking lots.

Features and Specifications:

- Delivers 500,000 BTU
- No smoke, no fumes
- Burn weeds, repair asphalt, seal tar, peel paint, remove road markings, melt ice, and thaw pipes
- Durable 10 ft. neoprene hose
- Accurate brass flow control shut-off valve
- Brass propane tank adaptor
- Spark ignitor
- Durable cast iron and steel nozzle (WB-101)
- Welded tube nozzle (WB-102)
- 31" Heavy-Duty Handle
- Meets NFPA 51 specifications
- Packaged in retail, self-service packaging
- One year warranty




WB-101-Heavy Duty



WB-102-Standard Duty


PART NO.	DESCRIPTION
WB-101	HEAVY DUTY
Replacement Parts:	
WB-100-13	Handle Assembly
WB-100-15	Hose Assembly
CB-529	Striker

PART NO.	DESCRIPTION
WB-102	STANDARD DUTY
Replacement Parts:	
WB-100-19	Handle Assembly
WB-100-15	Hose Assembly
CB-529	Striker

	2" DIA. X 1/4" NPT		2 1/2" DIA. x 1/4" NPT	
	PART NO.	GAUGE TYPE	PART NO.	GAUGE TYPE
<p>REGULATOR GAUGES & GAUGE CRYSTALS</p>  <p>G-25-4000W G-2-30RLW</p>	G-2-30RLW	30 PSIG Red Line	G-25-30RLW	30 PSIG Red Line
	G-2-30W	30 PSIG	G-25-30W	30 PSIG
	G-2-60W	60 PSIG	G-25-60W	60 PSIG
	G-2-100W	100 PSIG	G-25-100W	100 PSIG
	G-2-200W	200 PSIG	G-25-200W	200 PSIG
	G-2-400W	400 PSIG	G-25-400W	400 PSIG
	G-2-600W	600 PSIG	G-25-600W	600 PSIG
	G-2-1000W	1000 PSIG	G-25-2000W	1000 PSIG
	G-2-4000W	4000 PSIG	G-25-4000W	4000 PSIG
	G-2-CW	Lexan Crystal	G-25-CW	Lexan Crystal
	Installation Requires Teflon Tape or Oxygen Safe Compound To Guard Against Leakage			

PART NO.	DESCRIPTION	PSIG SCALE	SERVICE
G-204	"MC" Acetylene Tank	400	CGA-200
G-304	Commercial Acetylene	400	CGA-300
G-304H	Commercial Acetylene with Hand-Tight Nut	400	CGA-300
G-324	Carbon Dioxide	3000	CGA-320
G-324H	Carbon Dioxide with Hand-Tight Nut	3000	CGA-320
G-326	Nitrous Oxide	3000	CGA-326
G-346	Air	4000	CGA-346
G-346-H	Air, with Hand-Tight Nut	4000	CGA-346
G-354	Hydrogen	3000	CGA-350
G-354-H	Hydrogen with Hand-Tight Nut	3000	CGA-350
G-514	POL Acetylene, Straight	400	CGA-510
G-514A	POL Acetylene, 90°	400	CGA-510
G-514AH	POL Acetylene, 90° with Hand-Tight Nut	400	CGA-510
G-514H	POL Acetylene, with Hand-Tight Nut	400	CGA-510
G-524	"B" Tank Acetylene	400	CGA-520
G-544	Oxygen	3000	CGA-540
G-544A	Oxygen	4000	CGA-540
G-544H	Oxygen, with Hand-Tight Nut	3000	CGA-540
G-544AH	Oxygen, with Hand-Tight Nut	4000	CGA-540
G-584	Nitrogen, Argon, Helium	4000	CGA-580
G-584-H	Nitrogen, Argon, Helium, Hand-Tight Nut	4000	CGA-580
G-594	Industrial Air	4000	CGA-590

**CYLINDER PRESSURE TESTING GAUGES
2" BRASS**



G-584H